

# Model No. TM-370HD

**TYPE:** Self-supporting, extendable, motorized tubular mast.  
Designed for light weight antenna load.

**SPECIFICATIONS:**

TUBULAR MAST HEIGHT: Extended 68'-6". Retracted 27'-6".

WIND LOADING: Engineering analysis indicates the tower will support an antenna with an equivalent effective projected area of 28-ft<sup>2</sup> at a basic wind speed of 100 MPH, 3-second gust per ANSI/TIA-222-H. Exposure C, No Crest, Topo 1.

DEAD LOAD: The maximum antenna dead load is 600 lbs.

WEIGHT: The mast with the base weighs 3,050 pounds.

SECTIONS: The mast is made from 10", 8", and 6" pipe, Fy= 50 ksi

**DESCRIPTION:**

Tubular mast is complete with a 50:1 gearbox, 1 hp, 220V electric motor, 1/4" x 7 x 19 aircraft lift cable lift system and a hinged concrete base mount. The mast is designed to extend the tubular telescopic sections uniformly. A user's manual is included.


Tubular mast include a hinged base mount that is installed in concrete. This base mount allows the tower to be hinged at ground level and tilted into a vertical position.

The TM towers are hot-dipped galvanized after fabrication for maintenance free finish.


The top section of the mast is adapted to accept an accessory rotator cage assembly. If a rotator assembly is not used, the mast adapter can be ordered as an accessory item. All standard mast adapters accommodate a two (2) inch O.D. mast size.

**ACCESSORIES:**

- TM-370HD manual, Drawings, Calculations
- TM-370HD Concrete Base
- CO-3 for TM
- Work Platform
- Tilting Gin Pole
- Rotator Cage Assembly
- Cable Kit
- Motor Control Assembly
- TB-2 Thrust Bearing
- Remote Control Kit



CROSS SECTION



PART# 526-4000 \$14,134.00 USD